

# SAFETY DATA SHEET

Page 1 of 2

## TYRE DUSTING CHALK

Revision 0  
Revision date

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name TYRE DUSTING CHALK

Company



Telephone

Fax

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Talc (Hydrous Magnesium Silicate) (Talc, respirable dust)	90 - 100%	14807-96-6		

### 3. HAZARDS IDENTIFICATION

Main hazards No Significant Hazard

### 4. FIRST AID MEASURES

Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

### 5. FIRE FIGHTING MEASURES

Extinguishing media	Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards	Burning produces irritating, toxic and obnoxious fumes.
Protective equipment	Wear suitable respiratory equipment when necessary.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

Print date 17-Apr-2007

# TYRE DUSTING CHALK

Revision 0  
Revision date

## 7. HANDLING AND STORAGE

**Handling** Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

**Storage** Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

Talc (Hydrous Magnesium Silicate)  
(Talc, respirable dust)

WEL 8-hr limit ppm: -  
WEL 15 min limit ppm: -

WEL 8-hr limit mg/m<sup>3</sup>: 1  
WEL 15 min limit mg/m<sup>3</sup>: -

**Engineering measures** Ensure adequate ventilation of the working area.

**Hand protection** Chemical resistant gloves (PVC)

**Eye protection** In case of splashing, wear: Approved safety goggles.

**Protective equipment** Wear protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Description** Powder.

**Colour** White.

**Odour** Odourless.

**pH** 7

**Water solubility** insoluble in water.

## 10. STABILITY AND REACTIVITY

**Stability** Stable under normal conditions.

## 11. TOXICOLOGICAL INFORMATION

**Toxicological information** No known adverse health effects.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** No known adverse environmental effects.

## 13. DISPOSAL CONSIDERATIONS

**General information** Dispose of in compliance with all local and national regulations.

## 14. TRANSPORT INFORMATION

**Further information** The product is not classified as dangerous for carriage.

## 15. REGULATORY INFORMATION

**Labelling** Non hazardous.

**Risk phrases**

## 16. OTHER INFORMATION

**Further information** The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.