

SAFETY DATA SHEET

Page 1 of 3

RIMSEAL

Revision 0
Revision date

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

Product name

Company

RL AUTOMOTIVE

Unit D, Park 34
Southmead Industrial Estate
Didcot
OX11 7WB

Telephone

0870 850 8821

Fax

0870 850 8824

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Talc (Hydrous Magnesium Silicate) (Talc, respirable dust)	1 - 10%	14807-96-6		
C9-11 Alcohol Ethoxylate with 8MeO	1 - 10%	68439-45-2		Xn;R22 Xi;R41
Sodium hydroxide	0 - 0.5%	1310-73-2	215-185-5	C; R35

3. HAZARDS IDENTIFICATION

Main hazards

No Significant Hazard

4. FIRST AID MEASURES

Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing media	Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards	Burning produces irritating, toxic and obnoxious fumes.
Protective equipment	Wear suitable respiratory equipment when necessary.

Print date 18-May-2007

RIMSEALRevision 0
Revision date**6 ACCIDENTAL RELEASE MEASURES**

Personal precautions	Ensure adequate ventilation of the working area.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7 HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure limits**

Talc (Hydrous Magnesium Silicate) (Talc, respirable dust)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: 1 WEL 15 min limit mg/m3: -
Sodium hydroxide	WEL 8-hr limit ppm: - WEL 15 min limit ppm: -	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 2

Engineering measures	Ensure adequate ventilation of the working area.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	In case of splashing, wear: Approved safety goggles.
Protective equipment	Wear protective clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

Description	Paste.
Colour	Brown.
Odour	Characteristic.
Water solubility	insoluble in water.

10 STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11 TOXICOLOGICAL INFORMATION

Toxicological information	No known adverse health effects.
----------------------------------	----------------------------------

12 ECOLOGICAL INFORMATION

Ecotoxicity	No known adverse environmental effects.
--------------------	---

13 DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
----------------------------	---

14 TRANSPORT INFORMATION

Further information	The product is not classified as dangerous for carriage.
----------------------------	--

15 REGULATORY INFORMATION

Risk phrases	
---------------------	--

RIMSEALRevision 0
Revision date**16 OTHER INFORMATION**

Text of risk phrases in Section 2	R22 - Harmful if swallowed. R35 - Causes severe burns. R41 - Risk of serious damage to eyes.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. As the application of products is outside our control, the information is given without legal responsibility. Customers should test under their own conditions to ensure the products are suitable for their own requirements.
Labelling for contents	>= 15% - < 30% : soap.