



RL AUTOMOTIVE
www.rlatito.com



TYRE SERVICE PRODUCT SPECIALISTS



Page 1 of 5



Tel: 01235 835959

EFFECTIVE: 4/1/03
SUPERCEDES: 1/23/02

Abingdon. OX14 4RX. UK



MSDS NO.: 722
REVISION NO.: 5

TECH TIRE AND TUBE COMPOUND (incl. LITE)

MATERIAL SAFETY DATA SHEET

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TECH TIRE AND TUBE COMPOUND (incl. LITE)
CATALOG NUMBER(S): 722, 723, 722L, 723L
PRODUCT USE: TIRE LUBRICANT

FOR CUSTOMER SERVICE INFORMATION, CONTACT:
(740) 967-9015 or (800) 433-8324

EMERGENCY TELEPHONE NUMBER (24 hrs.): CHEMTREC (800) 424-9300
EMERGENCY TELEPHONE NUMBER (24 hrs.): CHEMTREC International (703) 527-3887

SECTION 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT (COMMON NAME)	CAS NO.	% (by wgt.)	OSHA PEL	ACGIH TLV	NIOSH REL	AIHA WEEL
Oleic Acid	112-80-1	27 - 30	*	*	*	*
Triethanolamine	102-71-6	20 - 23	*	5 mg/m3	*	*

EXPOSURE LIMITS ARE TIME WEIGHTED AVERAGES (TWA). SHORT-TERM EXPOSURE LIMITS (STEL) AND CEILING (C) ARE INCLUDED IF ESTABLISHED.

NOTES	
*	Not Established

SECTION 3. HAZARDS IDENTIFICATION

Emergency Overview:
Appearance & Odor: Light orange semi-solid, mild surfactant odor.
Health Hazards: May cause eye and skin irritation.
Physical Hazards: None available.
R-Phrases: R 36 Irritating to Eyes, R 38 Irritating to Skin

EYE CONTACT	Exposure to product may cause eye irritation. Symptoms include stinging, tearing, redness and swelling.
INHALATION	Not a normal route of entry.
INGESTION	Single dose oral toxicity is low. Symptoms may include: gastrointestinal irritation (nausea, vomiting, diarrhea).
SKIN CONTACT	Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry skin. Symptoms include: redness, burning, drying, cracking and skin burns.
TARGET ORGANS EFFECTED	CNS, liver, kidneys, skin, eyes

CARCINOGENICITY - LISTED BY:

ACGIH	No	IARC	No	NTP	No	OSHA	No
-------	----	------	----	-----	----	------	----

TECH TIRE AND TUBE COMPOUND (incl. LITE)
 TECHNICAL RUBBER COMPANY
 Page 2 of 5

MATERIAL SAFETY DATA SHEET

SECTION 4. FIRST AID MEASURES

EYE CONTACT	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes with water for at least 20 minutes while holding eyelids apart. If symptoms persist, seek medical attention.
INHALATION	Not a normal route of entry.
INGESTION	If swallowed, drink two large glasses of water to induce vomiting. Seek medical attention.
SKIN CONTACT	Wash exposed area with soap and water. If symptoms persist, seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD	Non Flammable
LEL	Not Established
UEL	Not Established
EXTINGUISHING MEDIA	Water, foam, carbon dioxide or dry chemical
SPECIAL FIRE FIGHTING PROCEDURES	Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires.
UNUSUAL FIRE AND EXPLOSION HAZARDS	Carbon monoxide and carbon dioxide may form as a result of heating or burning.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL	Absorb material with paper, vermiculite, floor absorbent, or other absorbing material. Transfer into approved container for disposal.
LARGE SPILL	Dike area of spill to prevent spreading. Absorb with appropriate materials. Transfer into approved containers for disposal. Toxic to fish. Do not dump into natural waterways.

SECTION 7. HANDLING AND STORAGE

Keep from freezing. Store in safe areas at room temperature. Do not incinerate containers.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION	Chemical splash goggles in compliance with OSHA regulations are advised, however OSHA regulations also permit other types of safety glasses. Consult your safety equipment representative.
RESPIRATORY PROTECTION	None should be required during normal use.
SKIN PROTECTION	Wear resistant gloves, such as: polyvinyl alcohol, nitrile.
ENGINEERING CONTROLS	Provide sufficient mechanical (general or local exhaust) ventilation to maintain exposure below OEL(s). Explosion-proof ventilation system is acceptable.
OTHER HYGIENIC AND WORK PRACTICES	Use good personal hygiene work practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

TECH TIRE AND TUBE COMPOUND (incl. LITE)
TECHNICAL RUBBER COMPANY
Page 3 of 5

MATERIAL SAFETY DATA SHEET

INITIAL BOILING POINT	214 ° F (101° C) @ 760.00 mm Hg
VAPOR PRESSURE	246.6 mm Hg @ 68°F
VAPOR DENSITY (air = 1)	>1
SPECIFIC GRAVITY (water = 1)	1.0
% VOLATILES	22.4
VOC CONTENT	1.86 lbs./gal (223.1 g/L)
EVAPORATION RATE	Slower than ether
pH	8.9
APPEARANCE	Light orange semi-solid
ODOR	Mild surfactant odor

SECTION 10. STABILITY AND REACTIVITY

STABILITY	Stable
HAZARDOUS POLYMERIZATION	Cannot occur
INCOMPATIBILITY (materials or conditions to avoid)	Strong oxidizers, strong acids
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon dioxide, carbon monoxide, various hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

No data is specifically available for this product and therefore this toxicological information is based on testing completed with ingredients

TOXICOLOGICAL DATA: **OLEIC ACID:** Oral Rat LD50: 74 gm/kg; Irritation: skin rabbit: 500 mg open mild. Investigated as a mutagen and tumorigen.
 TRIETHANOLAMINE: Oral Rat LD50: 8000 mg/kg; Irritation data: skin rabbit: 560 mg/24H mild; eye rabbit: 5620 ug severe. Investigated as a tumorigen and mutagen.

SECTION 12. ECOLOGICAL INFORMATION

This formulation has not been tested for environmental effects. This section will be updated as ecological reviews are completed.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of material should be done in accordance with all Federal (40 CFR Part 261), State and Local environmental control regulations.

TECH TIRE AND TUBE COMPOUND (incl. LITE)
TECHNICAL RUBBER COMPANY
Page 5 of 5

MATERIAL SAFETY DATA SHEET

INVENTORY STATUS (components):

Triethanolamine: Listed on the following international inventories: AICS (Australia), DSL (Canada), ECL (South Korea), EINICS (Europe), PICCS (Philippines).

Oleic Acid: Listed on the following international inventories: AICS (Australia), DSL (Canada), ECL (South Korea), EINICS (Europe), PICCS (Philippines).

SECTION 16. OTHER INFORMATION

NFPA AND HMIS RATINGS

HEALTH	1	FLAMMABILITY	0	REACTIVITY	0
---------------	---	---------------------	---	-------------------	---

MSDS No.: 722

Revision#: 5

Revision Date: 4/1/03

Revisions since last change (discussion): This MSDS has been revised to meet the requirements of the following standards: EEC Directive 2001/58/EC (91/155/EEC), ANSI Z400.1-1993 and Canadian WHMIS and CPR. There are no changes to the health, safety, precautionary data, or regulatory data. We do, however, encourage you to take the opportunity to reread the sheet and review the information. This MSDS complies with the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Prepared by: Tech International's Health and Safety Department

The information contained herein is based on data from our raw material suppliers and other sources and is believed to be accurate. This information is provided in compliance with national and local regulations, where applicable, to give warning of actual and assumed hazards, and to inform of generally applicable precautions and control measures which are known to Tech International. Tech International makes no warranty or representation that the information is accurate, reliable, complete or representative and the Buyer may rely on thereon only at Buyer's own risk. Tech International warrants only that it has made no effort to censor, other than trade secret information, or to conceal hazards of its products.

It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.

For 24-hour access to Tech International's MSDS documents:

- In North America call our Fax-on-Demand system at 888-612-8324, ext. 8324 (TECH).
- Outside North America call the international dialing code for the United States followed by 740 363-7715, ext. 3324. Then follow the instructions to leave a message with the requested document numbers and the country, city code and fax number.
- Also see www.techtirerepairs.com for latest MSDSs and instructions for fax-on-demand service.



HEALTH AND SAFETY DATA SHEETS

1. IDENTIFICATION OF SUBSTANCE OR PREPARATION.

TYRE BEAD LUBE (M034)

2. COMPOSITION/INFORMATION OF INGREDIENTS.

A BLEND OF:
 AQUA
 SODIUM AND AMINE TALLATES
 COCONUT DIETHANOLAMIDE
 NTA
 PRESERVATIVE
 DYE

3. HAZARDS IDENTIFICATION

KEEP OUT OF REACH OF CHILDREN
 THIS PRODUCT POSSES NO SIGNIFICANT HAZARD

4. FIRST AID MEASURES

INHALATION: N/A
SKIN CONTACT: N/A
EYE CONTACT: RINSE WITH PLENTY OF WATER FOR 10 MINS
INGESTION: WASH OUT MOUTH WITH PLENTY OF WATER. DO NOT INDUCE
 VOMITTING

ADDITIONAL INFORMATION:

5. FIRE FIGHTING MEASURES:

SUITABLE EXTINGUISHERS: USE EXTINGUISHERS SUITABLE FOR THE CAUSE OF FIRE
SPECIAL EQUIPMENT: SELF CONTAINED BREATHING APPARATUS. DUST MASK

6. ACCIDENTAL RELEASE MEASURES:

PERSONAL PRECAUTIONS: NON-SLIP FOOTWEAR
ENVIRONMENTAL PRECAUTIONS: PREVENT FROM ENTERING DRAINS AND WATER
 COURSES IN LARGE VOLUMES
CLEAN-UP PROCEDURES: IN QUANTITY: RINSE AWAY OR COLLECT INTO
 BINS AND DISPOSE OF IN ACCORDANCE TO LOCAL
 COUNCIL REGULATIONS FOR WASTE.

THE GRE-SOLVENT COMPANYPAGE 2 OF 3
M034**7. HANDLING AND STORAGE:****HANDLING REQUIREMENTS: SPILLAGES MUST BE CLEANED UP IMMEDIATELY****STORAGE CONDITIONS: DRY AMBIENT. PROTECT FROM FROST****8. EXPOSURE CONTROLS/PERSONAL PROTECTION:****ENGINEERING MEASURES: N/A****RESPIRATORY PROTECTION: N/A****HAND PROTECTION: N/A****EYE PROTECTION: N/A****SKIN PROTECTION: N/A****9. PHYSICAL AND CHEMICAL PROPERTIES:****STATE: CLEAR LIQUID****COLOUR: RED****ODOUR: DETERGENT****SOLUBILITY IN WATER: MISCIBLE****RELATIVE DENSITY: 1.01****pH: 9.0+/-0.5****10. STABILITY AND REACTIVITY:****CONDITIONS TO AVOID: EXTREMES OF TEMPERATURE****MATERIALS TO AVOID: OTHER CLEANING MATERIALS****HAZARDOUS DECOMPOSITION PRODUCTS: NONE****11. TOXICOLOGICAL INFORMATION:****SKIN CONTACT: LOW IRRITATION****EYE CONTACT: MODERATE IRRITATION****INGESTION: MODERATE IRRITATION****ADDITIONAL INFORMATION:****12. ECOLOGICAL INFORMATION: POSSES NO SIGNIFICANT HAZARD****13. DISPOSAL CONSIDERATIONS: DISPOSE OF IN ACCORDANCE WITH LOCAL REGULATIONS**

THE GRE-SOLVENT COMPANY

PAGE 3 OF 3
M034

14. TRANSPORT INFORMATION:

UN No:

IMDG:

ICAO/IATA:

ADR:

PROPER SHIPPING NAME: LIQUID TYRE BEAD LUBRICANT

ADDITIONAL INFORMATION:

15. REGULATORY INFORMATION:

SYMBOL:

R-PHRASES:

S-PHRASES: KEEP OUT OF REACH OF CHILDREN

ADDITIONAL INFORMATION:

16. OTHER INFORMATION:

ISSUE DATE: 13/11/02

ISSUE NUMBER: 1

The information contained in this HEALTH AND SAFETY DATA SHEET is based on knowledge available at the time of compilation and is intended to describe the product only in the terms of HEALTH AND SAFETY requirements. It does not signify any warranty with regard to specific properties or specifications.

AUTHORISED BY: JUSTIN TRUEMAN



RL AUTOMOTIVE
www.rlauto.com

TYRE SERVICE PRODUCT SPECIALISTS

Tel: 01235 835959

Abingdon. OX14 4RX. UK

Page 1 of 7

EFFECTIVE: 4/10/03
SUPERCEDES: 1/23/02

MSDS NO.: 735
REVISION NO.: 6

TECH BEAD SEALER

MATERIAL SAFETY DATA SHEET



SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TECH BEAD SEALER
 CATALOG NUMBER(S): 735, 735G, 735-5G, 735-55G
 PRODUCT USE: TIRE MOUNTING SEALANT

FOR CUSTOMER SERVICE INFORMATION, CONTACT:
 (740) 967-9015 or (800) 433-8324

EMERGENCY TELEPHONE NUMBER (24 hrs.): CHEMTREC (800) 424-9300
 CHEMTREC International (703) 527-3887

SECTION 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT (COMMON NAME)	CAS NO.	% (by vol.)	OSHA PEL	ACGIH TLV	NIOSH PEL
Light Aliphatic Naphtha	64742-89-8	>89	100 ppm TWA; 400 mg/m3 TWA	400ppm	100 ppm TWA; 400 mg/m3 TWA; 1000 ppm IDLH

EXPOSURE LIMITS ARE TIME WEIGHTED AVERAGES (TWA). SHORT-TERM EXPOSURE LIMITS (STEL) AND CEILING (C) ARE INCLUDED IF ESTABLISHED.

NOTES	
1	A complex stream of predominantly C6 to C9 hydrocarbons, exact composition varies. Occupational exposure limits based on limits for petroleum distillates/naphtha/rubber solvent.
*	Not Established

SECTION 3. HAZARDS IDENTIFICATION

Emergency Overview:
Appearance & Odor: Black liquid with a high viscosity. Strong solvent odor.
Health Hazards: May cause eye and skin irritation. Exposure to vapor mist is possible.
Physical Hazards: Flammable liquid. Do not use near open flame. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, etc.
R-Phrases: R11 Highly Flammable; R36/38 Irritating to eyes and skin
S-Phrases: S16 Keep away from sources of ignition - no smoking; S25 Avoid contact with eyes; S33 Take precautionary measures against static discharge; S51 Use only in well-ventilated areas
Hazard Symbol: F Highly Flammable

MATERIAL SAFETY DATA SHEET

EYE CONTACT	Exposure to product may cause eye irritation. Symptoms include stinging, tearing, redness and swelling.
INHALATION	Exposure to vapor or mist is possible. The short-term inhalation toxicity is low. Breathing small amounts of vapors during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful. Symptoms typically seen at air concentrations above the recommended exposure limits may include: irritation to nose, throat and respiratory system, metallic taste, muscle weakness. Initial central nervous system (CNS) excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects (confusion, impaired coordination, coma and possibly death).
INGESTION	Single dose oral toxicity is low. Symptoms may include: gastrointestinal irritation (nausea, vomiting, diarrhea), CNS depression.
SKIN CONTACT	Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry skin. Symptoms include: redness, burning, drying, cracking and skin burns.
TARGET ORGANS EFFECTED	CNS, liver, kidneys, skin, eyes

CARCINOGENICITY - LISTED BY:

ACGIH	No	IARC	No	NTP	No	OSHA	No
--------------	----	-------------	----	------------	----	-------------	----

SECTION 4. FIRST AID MEASURES

EYE CONTACT	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes with water for at least 20 minutes while holding eyelids apart. If symptoms persist, seek medical attention.
INHALATION	If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen. Keep person warm and quiet.
INGESTION	If swallowed, DO NOT induce vomiting. This material is an aspiration hazard. If person is drowsy or unconscious, place on left side with head down. Seek immediate medical attention.
SKIN CONTACT	Remove contaminated clothing. Wash exposed area with soap and water. Launder contaminated clothing before reuse. If symptoms persist, seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD	20.0 ° F (-6.7 ° C)
LEL	1.0%
UEL	8.0 %
EXTINGUISHING MEDIA	Foam, carbon dioxide or dry chemical
SPECIAL FIREFIGHTING PROCEDURES	Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires.
UNUSUAL FIRE AND EXPLOSION HAZARDS	Never use a welding or cutting torch on or near container (even when empty) because product (even just residue), can ignite explosively. All 5-gallon or larger metal containers should be grounded and bonded when material is being transferred. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources distant from the material handling point.

MATERIAL SAFETY DATA SHEET

SECTION 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL	Eliminate all sources of ignition (flames, pilot lights, electrical sparks) and absorb material on vermiculite, floor absorbent or other absorbent material.
LARGE SPILL	Eliminate all sources of ignition (flames, pilot lights, electrical sparks, etc.). Persons not wearing appropriate protective equipment should be excluded from area of spill until cleanup has been completed. Stop spill at source. Prevent material from entering drains, sewers, streams, or other bodies of water. Prevent from spreading by using dikes, booms, etc. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled material into clean, approved containers for recovery or disposal. Absorb unrecoverable material onto vermiculite, floor absorbent or other absorbent material, and transfer into clean approved containers for disposal.

SECTION 7. HANDLING AND STORAGE

Containers of this product may be hazardous when emptied. Since emptied containers retain product residues (vapors, liquid, and/or solids), all hazard precautions given in this data sheet must be observed.

- Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering, pouring or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form which may ignite the vapors of the flammable liquids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION	Chemical splash goggles in compliance with OSHA regulations are advised, however OSHA regulations also permit other types of safety glasses. Consult your safety equipment representative.
RESPIRATORY PROTECTION	If workplace exposure limit (s) of product or any component is exceeded (See Section 2), a NIOSH/MSHA approved respirator is advised in the absence of proper environmental control. OSHA regulations permit other NIOSH/MSHA approved respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.
SKIN PROTECTION	Wear resistant gloves, such as: polyvinyl alcohol, nitrile.
ENGINEERING CONTROLS	Provide sufficient mechanical (general or local exhaust) ventilation to maintain exposure below OEL(s). Explosion-proof ventilation system is acceptable.
OTHER PROTECTIVE EQUIPMENT	To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
OTHER HYGIENIC AND WORK PRACTICES	Use good personal hygiene work practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash before reuse.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INITIAL BOILING POINT	209 - 230 ° F (98.3 - 110 ° C) @ 760.00 mm Hg
VAPOR PRESSURE	110.50 mm Hg @ 100.00 ° F.
VAPOR DENSITY (air = 1)	3.30
SPECIFIC GRAVITY (water = 1)	0.75 @ 60.00 ° F

TECH BEAD SEALER
 TECHNICAL RUBBER COMPANY
 Page 4 of 7

MATERIAL SAFETY DATA SHEET

INITIAL BOILING POINT	209 - 230 ° F (98.3 - 110 ° C) @ 760.00 mm Hg
% VOLATILES	89.1%
VOC CONTENT	5.52 lbs./gal (660.9 g/L)
EVAPORATION RATE	3.6 (n-Butyl Acetate = 1)
pH	Not Applicable
APPEARANCE	Black liquid, high viscosity
ODOR	Strong solvent

SECTION 10. STABILITY AND REACTIVITY

STABILITY	Stable
HAZARDOUS POLYMERIZATION	Cannot occur
INCOMPATIBILITY (materials or conditions to avoid)	Strong oxidizers, strong acids
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon dioxide, carbon monoxide, various hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

No data is specifically available for this product and therefore this toxicological information is based on testing completed with ingredients.

TOXICOLOGICAL DATA LIGHT ALIPHATIC NAPHTHA: LD50 Oral Rat >25000mg/kg
 LC50 Inhalation Rat 14000-16000 ppm for 4 hours
 LD50 Dermal Rabbit >5000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. Biodegradable, rapid volatilization.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of material should be done in accordance with all Federal (40 CFR Part 261), State and Local environmental control regulations. In its unused state, the product exhibits the EPA hazardous waste characteristic for ignitability (RCRA waste code D001).

SECTION 14. TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME (49 CFR 172.101)	Adhesives
HAZARD CLASS (DOT, IATA)	3
HAZARD CLASS (IMO)	3
ID NUMBER	UN 1133

TECH BEAD SEALER
 TECHNICAL RUBBER COMPANY
 Page 5 of 7

MATERIAL SAFETY DATA SHEET

DOT PROPER SHIPPING NAME (49 CFR 172.101)	Adhesives
PACKING GROUP	II
ADDITIONAL DESCRIPTION	Petroleum Naptha
LABELS REQUIRED	Flammable Liquid (49 CFR 172.419)
2000 EMERGENCY RESPONSE GUIDEBOOK NO.	128
EmS NUMBER	3-05
REPORTABLE QUANTITY (DOT)	As D001 hazardous waste - 100 lbs. (45.4 kg.)

SECTION 15. REGULATORY INFORMATION

This product contains the following toxic substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (Emergency Planning and Community Right-To-Know Act) of 1986 and of 40 CFR Part 372:

CHEMICAL	CAS NO.	% COMPOSITION (by vol.)
Light Aliphatic Naphtha	64742-89-8	>89%

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 Chemical Substance Inventory List (40 CFR Part 710).

STATE REGULATIONS

The following chemicals are listed by individual states; other specific health and safety data in other sections of this MSDS may also be applicable for state requirements. For more details on state regulatory requirements contact the appropriate state.

California, Florida, New Jersey, Pennsylvania, Minnesota, and Massachusetts have the following chemical(s) on their Right-To-Know Chemical list:

n-Heptane (142-82-5)* 16%

- Component(s) of Light Aliphatic Naphtha

INTERNATIONAL REGULATIONS

INVENTORY STATUS (components):

LIGHT ALIPHATIC NAPHTHA: Listed on the following international inventories: AICS (Australia), DSL (Canada), ECL (South Korea), EINECS (Europe), PICCS (Philippines), and the Inventory of Existing Chemical Substances (China).

CANADA: WHMIS Class/Description: Class B2 Flammable Liquid
 Class D2B Other Toxic Effects - Skin Irritant

B Flammable

D Toxic



MATERIAL SAFETY DATA SHEET

SECTION 16. OTHER INFORMATION

NFPA and HMIS Ratings

HEALTH	1	FLAMMABILITY	3	REACTIVITY	0
---------------	---	---------------------	---	-------------------	---

MSDS No.: 735

For 24-hour access to Tech International's MSDS documents:

- In North America call our Fax-on-Demand system at 888-612-8324, ext. 8324 (TECH).
- Outside North America call the international dialing code for the United States followed by 740 363-7715, ext. 8324. Then follow the instructions to leave a message with the requested document numbers and the country, city code and fax number.
- Also see www.techtirerepairs.com for latest MSDSs and instructions for fax-on-demand service.

The information contained herein is based on data from our raw material suppliers and other sources and is believed to be accurate. This information is provided in compliance with national and local regulations, where applicable, to give warning of actual and assumed hazards, and to inform of generally applicable precautions and control measures which are known to Tech International. Tech International makes no warranty or representation that the information is accurate, reliable, complete or representative and the Buyer may rely on thereon only at Buyer's own risk. Tech International warrants only that it has made no effort to censor, other than trade secret information, or to conceal hazards of its products.

It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.

TECH BEAD SEALER
TECHNICAL RUBBER COMPANY
Page 7 of 7

MATERIAL SAFETY DATA SHEET